





# LOex Sens-Inox Tonga2 T92S

Electronic self-closing pillar tap, swivel spout, single-pipe inlet for cold or pre-mixed water or with UT-mixture according to EU-RL, HACCP, LMHV.

## Installation version DMK

		<b>Tendertext</b> Non-contact self-closing DN 15 Washable-tap, stainless steel satin; with rotating and lockable angular spout, aerator*, optosensor. For premixed water (UT mixer). Electronically controlled - integrated electronics (Donau/E8A, Weser/E9A).  - rotatable and lockable (Fig.) ii Outreach 190 mm Height of outlet opening from WT 235 mm Total height from WT 300 mm	<b>Operating version/ EAN-Number article-number</b>  for 12V low-voltage mains operation -  - integrated electronic "LOex Donau", B - external plug-in power supply unit - 12VDC 40 34154 02309 3 TG2SE8AST92ii19 5_DMK  -- integrated electronic "LOex Donau", C - external Meanwelltransformer - 12VDC 40 34154 02310 9 TG2SE8ALT92ii19 5_DMK
			<b>for Battery-operated - 6VDC</b> - integrated electronic "LOex Weser", E - external battery container(for 4x1,5 AA-batteries) 40 34154 02312 3 TG2SE9ABT92ii19 5_DMK

\*Economy jet regulator up to < 6 ltr/min  
a.A. against surcharge.



### Alternatives in powder coating

Surcharge u.r., no minimum order quantity.

Signalred matt	RAL 3001
Jetblack matt	RAL 9005
Light Grey matt	RAL 7035

Shades of colour in adjacent illustrations are not binding.




### Optional -



#### Remote control for sensor controls in direct current (DC)

For adapting electronic parameters and activating  
legionella flushing  
- for LOex Donau and LOex Weser electronics -

40 34154 01393 3 Zb 073

	<b>plugadaptor for LOex Donau 12VDC</b> B IP68-connector	Tapsocket - - rotateable and lockable (ii) Basisdiameter 59,5 mm Tap hole diameter 35 mm Quick fixing for panel thicknesses up to appr. 50 mm  Supply lines- Flexhose 3/8"cn ca. 500 mm  E8/E9 cable to source of energy ca. 800 mm cable to solenoid-valve ca. 500 mm	Self-closing wash-table tap DN 15, stainless steel (AISI304L) matt brushed; electronically controlled, with single-pipe inlet for premixed water; with rotatable and lockable spouts, jet regulator. Activated by the optosensor integrated into the fitting. The electronic control systems - <u>tap-integrated -</u> - LOex Donau[E8A] (12VDC, 9 W), - LOex Weser[E9A] (6VDC, 2 W) - Default programm, optional remote for activating legionella flushing and for adapting range, running times/intervals. - <u>Sources of energy -</u> - plugadaptors(12VDC)with IP68-connector,cable-adaptor - MWTrafo 12VDC, IP67 with powercord and IP68-connector - Batterycontainer for 4x1,5V AA-Alkalibatteries
	<b>Meanwell-transformer for LOex Donau 12VDC</b> C IP67; mains plug cable; IP68-connector Velcro or screw fastening		
	<b>Batterycontainer</b> E for 4x1,5V AA-Alkalibatteries, IP68-connector Velcro or screw fastening		
		<b>DMK-Mixer-Modul-Set</b> solenoid-valve Mixing by DMK mixer for direct mounting on angle-valve with integrated checkvalves WC/WH accessfilter f. angle-valve Connecting flexhose to WH-angle-valve  angle-valve(on-site)	
		<b>Also adaptable for pressure-less usage.</b>	
		<b>Also for de-mineralised water with electronic LOex Donau E8/24VDC and 24VDC-solenoid-valve in stainless-steel.</b>	

Subject to technical and price changes  
without prior notice. This offer is sub-  
ject to change.  
Our terms and conditions of sale and  
delivery apply exclusively.  
Status Nov 2025

Previous offers have lost their validity.  
Pricing: €/p.unit; ex warehouse, pac-  
ked; net.

Delivery dates on request.

Place of jurisdiction for registered tra-  
ders and persons under civil law:  
Frankfurt/M.

Scope of delivery: Fitting as described,  
ready for installation, complete.

EU-USID: DE111985600



**LOTZ Exim Trading**  
Sensortechnik für Küchen-, Catering-,  
Labor- und Sanitärbereiche.

*Es gibt nur wenig, was sich so bezahlt macht.-  
Für Sie und unsere Umwelt!*